

# AS0220 - UNILINK

Point to Point Link

Small Facia Enclosure

240Vac Mains or 24Vdc Powered

## Description

The UNILINK is a basic Hotline unit for connecting two simple 2W telephones over copper cable up to a distance of 6Km.

The unit can be powered from a plug top PSU or from a nominal 24V battery source.

All line feed, ring generator and supervisory tone circuits are contained in a single enclosure for stand alone installation.

Typical uses are for independent hotline systems for lift shafts, point to point links in field environments, surgeries etc.

Alternative versions are available for portable or fixed installations including a rugged enclosure version for field use.





## Technical

240Vac (via plugtop) or 24Vdc Powered  
BT631A for Telephone Connection  
Internal Ring Generator  
Provides Supervisory Tones

Weight - 700g  
Size - 85 x 85 x 60 mm

**REMOTE  
TELE**



**LOCAL  
TELE**



**Unilink**

**Up to 6Km**

ac or dc  
Power Source

**Alistair Douglas**  
10/12/03

OFFICE/DATA/DATASHEETS/AS0220 - UNILINK DATA SHT

**Keltel Comms Ltd**  
Thistle House, Union St, Kelso, Scotland, TD5 7DR  
Tel : +44 (0) 1573 228955 Fax : +44 (0) 1573 228951  
Email : sales@keltel.co.uk Web : www.keltel.co.uk