

AS3170 - Hotline 10

Instant Communications

Lamps to Show Port Status

48Vdc Powered

Description

The Hotline 10 unit provides a method of connecting up to ten remote telephones back to a single central control telephone with instant calling being created by lifting the telephone off-hook and selecting the active line key. Outgoing calls are made in the same manner with the additional facility to conference all active calls.

All remote devices are presented to the local unit as 4W E&M on RJ45 connectors but can be connected to FXS, FXO or AC15 circuits with the use of external interface adaptors.

Lamps and keys are provided on the base console to allow calling to the remote telephones and also indicate the remote telephone status including an ALL CALLS button to alert all external parties in the event of an emergency.

The functional diagram below shows two operational modes, one with the telephone interface equipment locally for operating over two wire lines and the other where a mux is used to distribute the hotline handsets to remote locations over a private closed network.

FRONT CONSOLE VIEW

FUNCTIONAL DIAGRAM Features 'ALL CALL' key for alerting all channels Bi-colour lamps to show line and call status •Calls can be 'toggled' and 'held' as required. Conference facility for all lines Hotline10 ■FXS. FXO or AC15 via external converters **Base Unit** •3U panel or stand-alone mounting Line Interface & Control Console up to 20m apart •Line Interfaces 'plug in' for rapid repair/replace AS50s HOUSED **MUX FOR CONN TO LINE** IN ASS10 **AS50** MUX ASB01 AS50 **NETWORK** MUX in ASB01 AS50 MUX ASB01 REMOTE **TELEPHONES**

REAR CONSOLE VIEW

Alistair Douglas 20/02/09

OFFICE/DATA/DATASHEETS/AS3170 - HOTLINE 10 DATA SHT

Heltel Comms Ltd
Thistle House, Union St, Kelso, Scotland, TD5 7DR
Tel: +44 (0) 1573 228955 Fax: +44 (0) 1573 228951
Email: sales@keltel.co.uk Web: www.keltel.co.uk